

Perno 16×80 mm Cat.0

Descrizione

Perno 16×80 mm Cat.0

Dati Tecnici :

- Diametro esterno perno: 16 mm
- Categoria: 0
- C Lunghezza totale perno:93 mm
- D Lunghezza: 86 mm
- E Diametro testa: 21 mm
- B Distanza da foro a testa: 78 mm
- F Diametro foro: 4 mm

Applicazioni :

Massey Ferguson:

- 122, 130, 133, 135, 140, 145, 148, 1505, 152, 155, 158, 165, 1805,
- 230, 231, 240, 243, 245, 25, 250, 253, 255, 260, 298,
- 30, 340, 35, 35 Gas / 35 Petrol, 35X, 362, 375, 383, 390, 390T, 393, 396, 398,
- 399,
- 550, 560, 65, 698, 699, 765, 825, 835, 865,
- TE20, TEA20, TED20, TEF20

White Oliver:

- 440, 550, 66, 660, 770, 88, 880, Super 44, SUPER 55, SUPER 77

Ford / New Holland :

- 2000, 2000 US Built, 2100, 2110, 2110LCG, 2110LCGInd., 2120, 2150, 2300,
- 230A, 230A US Built, 231, 231 US Built, 2310, 233, 250C,
- 2600, 2600 US Built, 260C, 2610, 2610 US Built, 2810, 2910, 2N, 3000, 3000 US
- Built, 3055, 3100, 3120, 3300, 3310, 333, 3330, 334, 335, 335 US Built, 340,
- 3400, 3400 US Built, 340A, 340B, 345C, 3500, 3500 US Built, 3550, 3600, 3600
- US Built, 3610, 3610 US Built, 3910, 4000, 4000 US Built, 4100, 4110, 4110 US
- Built, 4130, 4140, 4200, 4330, 4340, 4400, 4400 US Built, 4410,
- 445, 445 US Built, 445A, 445C, 450, 4500, 4500 US Built, 4600, 4600 US Built,
- 4610, 4610 US Built,
- 530A, 531, 531 US Built, 540, 540A, 540B, 541, 545, 545 US Built, 545C,
- 600, 601, 611, 620, 621, 630, 631, 640, 641, 650, 651, 660, 661, 671, 681,
- 700, 701, 740, 741, 771, 800, 801, 811, 820, 821, 841, 850, 851, 860, 861, 871,
- 881, 8N, 900, 901, 941, 950, 951, 961, 971, 981, 9N, Dexta, Jubilee, NAA, NAB,
- Power Major, Super Dexta, Super Major